

2 Middlefield Rd Columbine Valley, CO 80123 303-795-1434 Main 303-795-7325 Fax www.columbinevalley.org

Roofing Permit Application

This application is intended for roofing projects that do not require structural changes. Please use the *Building Permit Application with Plan Review* if you plan on making structural changes to your roof.

OwnerAddressPhoneEmail		AddressPhone							
					Project Address				
					Subdivision	Lot#		Block#	
					Valuation of described project—Includ	le labor and materia	als \$		
*Valuation of permit will be based on the sa Project Valuation Schedules", whichever is	-								
Columbine Valley has adopted the 2015	International Buildin	ig Code and the	2014 National E	lectric Code					
Roofing Details									
Please describe material used includin	- 1111								
Required Documents to process p	ermit:								
Signed Contract with Homeowner		HOA appr	oval						
All and any exterior modifications on proper permit without HOA approval	erty requires HOA ap	proval , The Tow	n of Columbine 1	Valley will not process					
No on street parking without a permit	between 3:00 a.m.	and 6:00 a.m.		Initial					
Door to Door solicitation is prohibited		-		Initial					
Advertising/Company signage is proh	ubited in Columbin	e Valley		Initial					
Signature			Date						



2 Middlefield Rd Columbine Valley, CO 80123 303-795-1434 Main 303-795-7325 Fax www.columbinevalley.org

Town of Columbine Valley Roofing Requirements

- Insulation—Insulation above roof decking shall be a continuous R25. Insulation in an attic or closed cavity shall be R38.
- Roof Ventilation—Enclosed attics and enclosed rafter spaces where a ceiling is directly applied to the underside of the rafter shall have cross ventilation. The minimum net free ventilating area shall be 1/150 square feet of the area of the vented space.
- Drip Edge Metal—Drip edge shall be provided at eaves and gable ends of roofs. Drip edge shall extend a minimum of 0.25 inch below the roof sheathing and extend up the roof deck minimum 2 inches onto the roof decking
- Ice Barrier—Ice barrier shall be used in lieu of normal underlayment and extend from the lowest edge of all roof surfaces to a point at least 24 inches inside of the building envelope.

When to call for inspections during your project

- Mid-Roof Inspection— When no more than 50% of roof covering is installed
- Final Inspection— When your project is complete
- A ladder is required on site for all inspections
- Inspections must be scheduled by 3pm the following day (Monday– Friday) the day before the desired inspection date. If no inspections are available for your preferred date, the next available inspection date will be offered to you.
- Inspection line—303-795-1434